

# LED STRIPLIGHTS

This range of LED striplights add subtle downlighting to your home. Ideal for mounting under kitchen units, shelves, wardrobes, display cabinets, alcoves and much more. These striplights simply click together, no tools required.

- Available in Cool White 4,000K and Warm white 3,000K
- Can combine 10 LED & 20 LED fittings
- Fittings can be close butted or linked with adjustable link lead
- A selection of accessories are available such as dimmers and photocells. Please see back for details
- Suitable for indoor use only



The Maximum number of fittings in one run:-

DRIVERS	35cm	60cm
LED125D (Supplied with starter kit)	6	3
LED250D (Sold separately)	10	6

	STARTER KITS	ADD ON KITS 2 X 35CM	ADD ON KITS 1 X 60CM
	<p><b>LED125D-C</b> (Warm White)</p> <p><b>LED250D-C</b> (Cool White)</p>	<p><b>LED125D-2N-C</b> (Warm White)</p> <p><b>LED250D-2N-C</b> (Cool White)</p>	<p><b>LED125D-60N-C</b> (Warm White)</p> <p><b>LED250D-60N-C</b> (Cool White)</p>
<b>Contents</b>	2 x 35cm LED Striplights, 1 x 30cm Link Lead, 8 x crimps, 2 x Female Connectors, 2 x Male Connectors, 8 x Mounting Clips & Screws, 1 x In-line LED Driver	2 x 35cm LED Striplights, 2 x 30cm Link Lead, 8 x crimps, 2 x Female Connectors, 2 x Male Connectors, 8 x Mounting Clips & Screws	1 x 60cm LED Striplights, 1 x 30cm Link Lead, 8 x crimps, 2 x Female Connectors, 2 x Male Connectors, 8 x Mounting Clips & Screws
<b>Product Dimensions</b>	Length 345 x Dia 12mm		Length 588 x Dia 12mm
<b>Product weight</b>	0.312Kg	0.168Kg	0.193Kg
<b>Barcode</b>	<p>LED125D-C - 5012739 644054</p> <p>LED250D-C - 5012739 644085</p>	<p>LED125D-2N-C - 5012739 644061</p> <p>LED250D-2N-C - 5012739 644092</p>	<p>LED125D-60N-C - 5012739 644078</p> <p>LED250D-60N-C - 5012739 644108</p>
<b>Cable Length</b>	Input - 1.2m/Output - 2.1m	-	-
<b>Lumens</b>	Per 35cm Strip = 150 lm		Per 60cm Strip = 300 lm
<b>Lamp Type</b>	LED		
<b>Lamp life expectancy</b>	25,000 hrs		
<b>LED's Array</b>	10		20
<b>Colour Temperature</b>	Cool White - 4,000k Warm White - 3,000k		
<b>Input Voltage</b>	12V DC		
<b>Power Consumption</b>	2.8W per 35cm strip		4.5W per 60cm strip
<b>Main housing material</b>	Aluminium		
<b>Guarantee</b>	3 Years		
<b>Certification &amp; Conformity</b>	BS EN 60950-1		

TECHNICAL DATA SHEET

These easy plug-in accessories for the LED Striplight Range enable local control of light level.




**LEDPCN**



**LEDPIRN**



**LEDDIMN**



**LEDLEADN**



**LEDD125D / LED250D**

	<b>LED125D</b>	<b>LED250D</b>	<b>LEDDIMN</b>	<b>LEDPCN</b>	<b>LEDPIRN</b>	<b>LEDLEADN</b>
<b>Contents</b>	LED DRIVER The Maximum number of fittings in one run:- 6 x 35cm or 3 x 60cm	LED DRIVER The Maximum number of fittings in one run:- 10 x 35cm or 6 x 60cm	In-line Dimmer	In-line photocell	In-line PIR	Link Lead
<b>Product Dimensions</b>	Input lead 1.2M Output lead 2.1M	Input lead 1.2M Output lead 2.1M	Cable length each side 15cm	Cable length each side 15cm	Cable length each side 15cm	30cm
<b>Product weight</b>	0.163Kg	0.200Kg	0.057Kg	0.058Kg	0.055Kg	0.008Kg
<b>Product Information</b>	-	-	IP20	IP20	Max Range 5M On time 4 mins max	-
<b>Barcode</b>	5012739644276	5012739644283	5012739644344	5012739644368	5012739644375	5012739644351
<b>Rated Current</b>	1250mA	2500mA	2.5A	2.5A	2.5A	-
<b>Input Voltage</b>	230V	230V	12V DC	12V DC	12V DC	
<b>Guarantee</b>	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year
<b>Certification &amp; Conformity</b>	EN 60950-1		-	-	-	-