


DELTA RANGE - IP20 LED Battens

- + Steel body construction, Opal polycarbonate diffusers
- + High LED chip efficiency
- + Integrated driver
- + Compact design
- + Instant start
- + Emergency options now available in 5ft & 6ft fittings - please visit www.greenbrook.co.uk
- + High output options in the same footprint

TECHNICAL DATA SHEET



	LEDBAT4	LEDBAT5	LEDBAT6	LEDBAT4H	LEDBAT5H	LEDBAT6H
Description	4ft Batten	5ft Batten	6ft Batten	4ft Batten (High Output)	5ft Batten (High Output)	6ft Batten (High Output)
Barcode	5012739645839	5012739645853	5012739645877	5012739645846	5012739645860	5012739645884
Wattage	18W	24W	32W	36W	48W	64W
Power Rating	220V/240V AC ~50Hz					
Colour Temperature	4,000K					
Class	I					
IP Rating	IP20					
Lamp Type	LED Non-replaceable					
Fitting Lumens	2500	3100	4000	4200	5500	7900
Total Lumens of Light Source	2735 lm at 180°	3498 lm at 180°	4700 lm at 180°	4684 lm at 180°	6109 lm at 180°	9111 lm at 180°
Energy Efficiency Class	E					
Operating Temperature	-15°C to +50°C					
SDCM	2.6	2.7	2.6	5.8	4.6	5.7
LED Light Source	NDLS (Non-direction Light Source)					
Main Housing	Steel Body with Polycarbonate Diffuser					
Dimensions	L1190 x W53 x H64mm	L1485 x W53 x H64mm	L1758 x W53 x H64mm	L1190 x W53 x H64mm	L1485 x W53 x H64mm	L1758 x W53 x H64mm
Mounting Options	BESA mount or Screw fixings					
Knockouts	20mm knockout at ends of fitting & 1 x 20mm knockout at the back					
Weight (g)	1030g	1281g	1510g	1106g	1342g	1674g
Life Span	30,000 hours					
Guarantee	3 Years					
Conforms To	BS EN60598-1 BS EN60598-2-1					



Replaceable (LED Only) light source by professional



Replaceable control gear by a professional

For non-user replaceable light sources:- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.