

CABLE CLIPS with PH2 & T20 Screws for Round Cable

- + For concrete and tile: screw directly into 4 mm hole – no plug required
- + For 13 mm single-layer plasterboard: mount using yellow plug (KP yellow 320015)
- + For double-layer plasterboard – no plug required
- + For 13 mm single-layer plasterboard on metal profile – no plug required
- + For wood, fibreboard and plywood: screw directly into material
- + For aerated concrete: mount using yellow plug (KP yellow 320015). For densities above 600, screw directly into concrete
- + Installation torque: max 6.3 Nm in concrete C20/25



Atmospheric corrosivity categories according to EN ISO 12944-2 with examples of typical environments.

| Corrosivity Category | Environmental corrosion | Examples of typical outdoor environments | Examples of typical indoor environments |
|----------------------|-------------------------|---|--|
| C1 | Very low | – | Heated areas with dry air and minor amounts of impurities (e.g. offices, shops, schools, hotels) |
| C2 | Low | Environments with low levels of atmospheric pollution. Rural areas. | Unheated areas with varying temperature and humidity levels. Low frequency of condensation and low level of atmospheric pollution, e.g. sports halls and warehouses. |
| C3 | Moderate | Environments with low salinity or moderate atmospheric pollution. Urban areas and light industrial areas. Areas with certain coastal influence. | Areas with moderate air humidity and some atmospheric pollution from production processes (e.g. breweries, dairies, laundries, etc.) |
| C4 | High | Environments with moderate salinity or significant atmospheric pollution. Industrial and coastal areas. | Areas with high air humidity and high atmospheric pollution from production processes (e.g. chemical plants, swimming pools, shipyards, etc.) |
| C5-I | Very high (Industrial) | Industrial areas with high air humidity and aggressive atmosphere. | Areas with almost constant condensation and high levels of atmospheric pollution. |
| C5-M | Very high (Maritime) | Coastal and offshore areas with high salinity. | Areas with almost constant condensation and high levels of atmospheric pollution. |

CABLE CLIPS with PH2 & T20 Screws for Round Cable



Material:



Impact resistant, UV-stabilized polypropylene, halogen free.

Screw:



Strong concrete screw, Corrosion Class C4, PH2/TORX 20
Can be installed both indoors and outdoors.



Cable clips with PH2 screw for round cable

| Ref. No. | Type | Screw PH2 (mm)  | Barcode | Colour | Drill Ø (mm)  | Box Qty |
|----------|---------------|--|----------------|--------|--|---------|
| 170065 | SC C4 7-10 W | 5 x 33 | 5701925171015 | White | 4 | 100 |
| 170075 | SC C4 7-10 B | 5 x 33 | 5701925 171282 | Black | 4 | 100 |
| 170005 | SC C4 10-14 W | 5 x 40 | 5701925170117 | White | 4 | 100 |
| 170015 | SC C4 10-14 B | 5 x 40 | 5701925170780 | Black | 4 | 100 |
| 170025 | SC C4 14-18 W | 5 x 40 | 5701925170315 | White | 4 | 100 |
| 170035 | SC C4 14-18 B | 5 x 40 | 5701925170889 | Black | 4 | 100 |
| 170045 | SC C4 18-22 W | 5 x 45 | 5701925170513 | White | 4 | 50 |
| 170055 | SC C4 18-22 B | 5 x 45 | 5701925170988 | Black | 4 | 50 |
| 170100 | SC C4 22-26 W | 5 x 45 | 5701925170100 | White | 4 | 50 |
| 170110 | SC C4 22-26 B | 5 x 45 | 5701925170025 | Black | 4 | 50 |

Cable clips with T20 screw for round cable

| Ref. No. | Type | Screw T20 (mm)  | Barcode | Colour | Drill Ø (mm)  | Box Qty |
|----------|---------------|--|---------------|--------|--|---------|
| 180000 | SC C4 7-10 W | 5 x 33 | 5701925180000 | White | 4 | 100 |
| 180024 | SC C4 7-10 B | 5 x 33 | 5701925180024 | Black | 4 | 100 |
| 180086 | SC C4 10-14 W | 5 x 40 | 5701925180086 | White | 4 | 100 |
| 180109 | SC C4 10-14 B | 5 x 40 | 5701925180109 | Black | 4 | 100 |
| 180116 | SC C4 14-18 W | 5 x 40 | 5701925180116 | White | 4 | 100 |
| 180130 | SC C4 14-18 B | 5 x 40 | 5701925180130 | Black | 4 | 100 |
| 180147 | SC C4 18-22 W | 5 x 45 | 5701925180147 | White | 4 | 50 |
| 180161 | SC C4 18-22 B | 5 x 45 | 5701925180161 | Black | 4 | 50 |
| 180178 | SC C4 22-26 W | 5 x 45 | 5701925180178 | White | 4 | 50 |
| 180192 | SC C4 22-26 B | 5 x 45 | 5701925180192 | Black | 4 | 50 |