SAFETYSURE

- RCD Plug / RCD Adaptor / RCD In-line



- Suitable for use with all makes of electrical & gardening appliances
- Electrically latched will need to be reset after power loss
- Cuts the power for added protection against electrocution
- All products have a separate 'Test' & 'Reset' buttons
- Large, clear indicator window, flags Red (RCDA & L) or Orange (RCDP) when 'On'









Tel: 01279 772 772 Email: sales@greenbrook.co.uk www.greenbrook.co.uk



	RCDA	RCDP	RCDL
Product Description	RCD Adaptor	RCD Plug	RCD In-line
Barcode	5012739627156	5012739627163	5012739634451
Product Finish	White	White	Black
Product Weight	140g	140g	213g
Product Dimensions	H140 x W59 x 46mm	H123 x W49.5 x 54mm (not including cable gland 24mm)	H210 x W60mm
Voltage	230V AC ~ 50Hz		230/250V AC ~ 50/60Hz
Max Operating Current	13A (13A Inductive)		13A (4A Inductive)
IP Rating	IP40	IP54	IP55
No of Poles	2	2	2
Rated Trip Current	30mA		
Typical Trip Speed	Less than 40mS (typical)		
RCD Contact Break	Double Pole		
Latching	Electrical - Needs to be reset after Power Loss (Active)		
Responsive To	Pulsating DC earth faults - Type A RCD		
Main Housing Material	Polycarbonate		
Guarantee	1 Year		
Conforms To	BS 7071 8	3 BS 1363	BS 7071 & BS 61543